




NTN Bearing Rolamentos do Brasil Ltda.



skf SAFS 23026 KAT x 4.7/16 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAFS 23026 KAT x 4.7/16

SAFS 23026 KAT x 4.7/16 Bearing 2D drawings and 3D CAD models

d_a	112.713 mm
D_a	200 mm
C_a	62.789 mm
A_1	120.65 mm
A_2	231.775 mm
b_a	51.594 mm
H	244.475 mm
H_1	125.425 mm
H_2	52.388 mm
J min.	320.675 mm
J max.	368.3 mm
J_1	69.85 mm
L	419.1 mm
N_1	24.209 mm
R_1	73.025 mm
R_2	31.75 mm
R_G	3/8 NPT
P_G	1/4 NPT
h	40.922 mm
Housing	SAFS 026 KA
Stabilizing ring	2 x 38151-26
Taconite seal	TER 117
End plug (suffix Y)	EPR 15
Max. speed for Taconite seal	700 r/min
P_{60°	178 kN



NTN Bearing Rolamentos do Brasil Ltda.

P _{90°}	107 kN
P _{120°}	66.7 kN
P _{150°}	59.6 kN
P _{180°}	72.5 kN
P _a	20.2 kN
Mass pillow block	50.8 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	0.75 in
Initial grease fill	232.47 g