




NTN Bearing Rolamentos do Brasil Ltda.



skf SAF 1622 x 4 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 1622 x 4 T

SAF 1622 x 4 T Bearing 2D drawings and 3D CAD models

d_a	101.6 mm
D_a	240 mm
C_a	89.789 mm
A_1	133.35 mm
A_2	273.05 mm
b_a	48.419 mm
H	287.337 mm
H_1	152.4 mm
H_2	60.325 mm
J min.	371.475 mm
J max.	406.4 mm
J_1	82.55 mm
L	466.725 mm
N_1	25.4 mm
R_1	79.375 mm
R_2	36.513 mm
R_G	1/2 NPT
P_G	1/4 NPT
h	63.5 mm
Housing	SAF 622
Stabilizing ring	2 x SR-1622
Taconite seal	TER 110
End plug (suffix Y)	EPR 13
Max. speed for Taconite seal	775 r/min
P_{60°	189 kN



NTN Bearing Rolamentos do Brasil Ltda.

P_{90°	113 kN
P_{120°	73.8 kN
P_{150°	68.1 kN
P_{180°	84.5 kN
P_a	16.7 kN
Mass pillow block	62.8 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	1220 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.875 in
Initial grease fill	765.45 g