




# NTN Bearing Rolamentos do Brasil Ltda.



skf SSAFS 23034 KATLC x 6 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SSAFS 23034 KATLC x 6

SSAFS 23034 KATLC x 6 Bearing 2D drawings and 3D CAD models

$d_a$	152.4 mm
$D_a$	259.999 mm
$C_a$	86.614 mm
$A_1$	149.225 mm
$A_2$	193.675 mm
$b_a$	64.294 mm
H	298.45 mm
$H_1$	152.4 mm
$H_2$	60.325 mm
L	511.175 mm
$R_1$	87.313 mm
$R_2$	38.1 mm
$R_G$	3/4 NPT
$P_G$	1/4 NPT
h	44.45 mm
Housing	SSAFS 034 KA
Stabilizing ring	2 x SR-0-24
Labyrinth ring	2 x LOR 141
PosiTrac Plus contact element	2 x B10724-140
End plug (suffix Y)	EPR 18
Max. speed for PosiTrac Plus seal	950 r/min
$P_{60^\circ}$	301 kN
$P_{90^\circ}$	180 kN
$P_{120^\circ}$	116 kN



## NTN Bearing Rolamentos do Brasil Ltda.

$P_{150^\circ}$	105 kN
$P_{180^\circ}$	127 kN
$P_a$	34 kN
Mass pillow block	92 kg
Cap bolt	7/8-9 UNC
Cap bolt recommended tightening torque	813.5 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	481.95 g