



NTN Bearing Rolamentos do Brasil Ltda.



skf FSAF 1613 x 2.1/8 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. FSAF 1613 x 2.1/8 T

FSAF 1613 x 2.1/8 T Bearing 2D drawings and 3D CAD models

d_a	53.975 mm
D_a	140 mm
C_a	57.785 mm
A_1	88.9 mm
A_2	209.55 mm
b_a	32.544 mm
H	167.481 mm
H_1	88.9 mm
H_2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
J_1	53.975 mm
L	330.2 mm
N_1	19.05 mm
R_1	53.181 mm
R_2	21.431 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	36.513 mm
Housing	FSAF 613
Stabilizing ring	2 x SR-1613
Taconite seal	TER 31
End plug (suffix Y)	EPR 7
Max. speed for Taconite seal	1400 r/min
P_{60°	60.5 kN



NTN Bearing Rolamentos do Brasil Ltda.

P_{90°	36 kN
P_{120°	21.8 kN
P_{150°	19.6 kN
P_{180°	23.1 kN
P_a	6.49 kN
Mass pillow block	17.1 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	175.77 g