



NTN Bearing Rolamentos do Brasil Ltda.

45 mm x 85 mm x 23 mm SNR
NUP.2209.E.G15 Single row cylindrical roller
bearings

Bearing No. NUP.2209.E.G15

d	45 mm
D	85 mm
B	23 mm
E	76.5 mm
F	54.5 mm
d1	59 mm
D1	73.3 mm
rs min	1.1 mm
r1s min	1.1 mm
Radial clearance class	CN
Mass (without HJ ring)	0.56 kg
Dynamic load, C	77.7 kN
Static load, C0	87 kN
Fatigue limit load, Cu	10.6 kN
Nref	5,700 rpm
Nlim	9,900 rpm
Min operating temperature, Tmin	-20 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.79 Hz
Characteristic outer ring frequency, BPF0	6.24 Hz

NUP.2209.E.G15 Bearing 2D drawings and 3D CAD
models



NTN Bearing Rolamentos do Brasil Ltda.

Characteristic inner ring frequency, BPF1	8.76 Hz
da min	51.5 mm
dc min	61 mm
Da max	78.5 mm
ra max	1 mm
r1a max	1 mm