



NTN Bearing Rolamentos do Brasil Ltda.

50 mm x 90 mm x 23 mm NTN NUP2210C3U Single row cylindrical roller bearings

Bearing No. NUP2210C3U

d	50 mm
D	90 mm
B	23 mm
E	80.4 mm
F	60.4 mm
d1	64.6 mm
rs min	1.1 mm
r1s min	1.1 mm
Radial clearance class	C3
Mass (without HJ ring)	0.62 kg
Dynamic load, C	64 kN
Static load, C0	73.5 kN
Fatigue limit load, Cu	9 kN
Nlim (oil)	8,100 rpm
Nlim (grease)	6,900 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.9 Hz
Characteristic outer ring frequency, BPF0	6.44 Hz
Characteristic inner ring frequency, BRF1	8.56 Hz

NUP2210C3U Bearing 2D drawings and 3D CAD models



NTN Bearing Rolamentos do Brasil Ltda.

da min	56.5 mm
dc min	67 mm
Da max	83.5 mm
ra max	1 mm
Category	Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.598
Product Group	B04144