



# NTN Bearing Rolamentos do Brasil Ltda.



SI 30 C Bearing 2D drawings and 3D CAD models

skf SI 30 C Spherical plain bearings and rod ends with a female thread

Bearing No. SI 30 C

Category	Spherical Plain Bearings - Rod Ends
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.05
EAN	7316577002983
Product Group	B04286
Stud Profile	Female
Mounting Thread	M30 X 2
Thread Direction	Right Hand
Rolling Element	Spherical Plain
Material - Outer Member	Steel
Material - Ball	Steel
Material - Liner	Teflon Sintered Bronze
Relubricatable	No
Enclosure	Open
Other Features	3 Piece   Zinc Plated Outer   Self Lubricating   Maintenance Free
Long Description	30MM Bore; 20MM House Width; Female Stud Profile; M30 X 2; Right Hand Thread Direction; Spherical Plain Bearing; Steel Outer Member; Steel Ball; Teflo
Inch - Metric	Metric
Category	Plain Bearing Spherical Rod



## NTN Bearing Rolamentos do Brasil Ltda.

	Ends
UNSPSC	31171508
Harmonized Tariff Code	8483.30.80.55
Noun	Bearing
Keyword 3	Rod End
Keyword String	Plain Spherical Rod End
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	SI 30 C
Weight / LBS	2.315
Ball Width	0.866 Inch   22 Millimeter
d	1.181 Inch   30 Millimeter
Housing Width	0.787 Inch   20 Millimeter
bore diameter:	30 mm
ball material:	Steel
misalignment angle:	6 °
race material:	Bronze
shank thread length:	45 mm
radial static load capacity:	118 kN
rod end type:	Female Threaded
operating temperature range:	-50 to +150 ° F
shank thread size:	M30x2
head diameter:	75 mm
thread direction:	Right Hand
head width:	20 mm
grade:	Commercial/Industrial
ball width:	22 mm
lubrication type:	Maintenance Free/Self-Lubricating
length to ball center:	110 mm
housing material:	Zinc-Plated Steel
standards met:	ISO 12240-4:1998, ISO 965-1:1998



## NTN Bearing Rolamentos do Brasil Ltda.

d	30 mm
d <sub>2</sub> max.	75 mm
B	22 mm
G	M 30x2
C <sub>1</sub> max.	20 mm
h <sub>1</sub>	110 mm
	6 °
d <sub>k</sub>	40.7 mm
d <sub>4</sub>	42 mm
l <sub>3</sub> min.	45 mm
l <sub>4</sub> max.	149 mm
l <sub>5</sub>	19 mm
l <sub>7</sub> min.	36 mm
w	36 mm
r <sub>1</sub> min.	0.6 mm
Basic dynamic load rating C	65.5 kN
Basic static load rating C <sub>0</sub>	118 kN
Specific dynamic load factor K	100 N/mm <sup>2</sup>
Material constant K <sub>M</sub>	1400
Mass rod end	1.05 kg