




# NTN Bearing Rolamentos do Brasil Ltda.



95 mm x 130 mm x 18 mm skf 71919  
CE/HCP4AL Super-precision Angular contact ball bearings

Bearing No. 71919 CE/HCP4AL

71919 CE/HCP4AL Bearing 2D drawings and 3D CAD models

Size	130x95x18 mm
Bore Diameter	130 mm
Outer Diameter	95 mm
Width	18 mm
d	95 mm
D	130 mm
B	18 mm
d <sub>1</sub>	106 mm
d <sub>2</sub>	102.9 mm
D <sub>1</sub>	119.22 mm
b	2.6 mm
C <sub>1</sub>	9.3 mm
C <sub>2</sub>	3 mm
C <sub>3</sub>	3 mm
r <sub>1,2</sub> - min.	1.1 mm
r <sub>3,4</sub> - min.	0.6 mm
a	25 mm
d <sub>a</sub> - min.	101 mm
d <sub>b</sub> - min.	98.2 mm
D <sub>a</sub> - max.	124 mm
D <sub>b</sub> - max.	126.8 mm
r <sub>a</sub> - max.	1 mm
r <sub>b</sub> - max.	0.6 mm
d <sub>n</sub>	108.5 mm



## NTN Bearing Rolamentos do Brasil Ltda.

Basic dynamic load rating - C	30.7 kN
Basic static load rating - C <sub>0</sub>	25.5 kN
Fatigue load limit - P <sub>u</sub>	0.98 kN
Limiting speed for grease lubrication	16000 r/min
Limiting speed for oil lubrication	25000 mm/min
Ball - D <sub>w</sub>	11.112 mm
Ball - z	25
G <sub>ref</sub>	7.3 cm <sup>3</sup>
Calculation factor - f <sub>0</sub>	8.6
Preload class A - G <sub>A</sub>	166 N
Preload class B - G <sub>B</sub>	500 N
Preload class C - G <sub>C</sub>	995 N
Calculation factor - f	1.18
Calculation factor - f	1
Calculation factor - f <sub>2A</sub>	1
Calculation factor - f <sub>2B</sub>	1.05
Calculation factor - f <sub>2C</sub>	1.09
Calculation factor - f <sub>HC</sub>	1.01
Preload class A	75 N/micron
Preload class B	119 N/micron
Preload class C	163 N/micron
d <sub>1</sub>	106 mm
d <sub>2</sub>	102.9 mm
D <sub>1</sub>	119.22 mm
C <sub>1</sub>	9.3 mm
C <sub>2</sub>	3 mm
C <sub>3</sub>	3 mm
r <sub>1,2</sub> min.	1.1 mm



## NTN Bearing Rolamentos do Brasil Ltda.

$r_{3,4}$ min.	0.6 mm
$d_a$ min.	101 mm
$d_b$ min.	98.2 mm
$D_a$ max.	124 mm
$D_b$ max.	126.8 mm
$r_a$ max.	1 mm
$r_b$ max.	0.6 mm
$d_n$	108.5 mm
Basic dynamic load rating C	30.7 kN
Basic static load rating $C_0$	25.5 kN
Fatigue load limit $P_u$	0.98 kN
Attainable speed for grease lubrication	16000 r/min
Attainable speed for oil-air lubrication	25000 r/min
Ball diameter $D_w$	11.112 mm
Number of balls z	25
Reference grease quantity $G_{ref}$	7.3 cm <sup>3</sup>
Preload class A $G_A$	166 N
Static axial stiffness, preload class A	75 N/ $\mu$ m
Preload class B $G_B$	500 N
Static axial stiffness, preload class B	119 N/ $\mu$ m
Preload class C $G_C$	995 N
Static axial stiffness, preload class C	163 N/ $\mu$ m
Calculation factor f	1.18
Calculation factor $f_1$	1
Calculation factor $f_{2A}$	1
Calculation factor $f_{2B}$	1.05
Calculation factor $f_{2C}$	1.09
Calculation factor $f_{HC}$	1.01



## NTN Bearing Rolamentos do Brasil Ltda.

Calculation factor $f_0$	8.6
Mass bearing	0.48 kg